

MINI LIGHT 2-axle 2xPH1100HO



GENERAL

This Mini Light 2xPH is a bigger version of the Mini Light. This model has two preheaters as twin or separate units. The preheaters are independent from each other.

This model has two alternative filling system, either with big-bags or with the pump-filling system when filling from separate boiler truck

We combine the full RME technology and safety issue in all aspects. The machine is still operated from inside the truck cabin.

Also this model is equipped with the well known RME-pump, a hydraulically driven compressor, camera system for supervision, heat-oil system and glass bead system.

Application can be done on both sides with the newly developed transversal gun carrier, which is hydraulically movable from side to side. The gun carrier is operated from the truck cabin. The advantages of this solution are that only one extruder /set of spray guns are kept warm all the time besides the economy aspect to have only one extruder/set of spray guns to maintain.

The Mini Light 2xPH is a high capacity machine with sets ups for extruder, spray or Flexidot.

TECHNICAL SPEC.

Length:	~7,0 m
Wheel base chassie:	min 4,3 m
Width:	2,55 m
Height:	3,7-3,9 m
Weight, tara incl truck:	13.500 kg
Weight, allowed:	18.000 kg
Melting set:	2x1.100L
Control Box:	RME
Extruder:	max 50cm
Spray block:	max 3pc
Flexidot:	max 45cm
Bead guns:	2-3pc
Bead tank:	415-470L
Production pump:	RME 120L/min
Compressor:	Hydraulic 5-7m ³
Pointer:	Hydraulic/Pneumatic
Burners:	Riello 230V
Temp regulators:	CAN-BUS