

MINI LIGHT 2-axle PH1900HO



GENERAL

This Mini Light is a bigger version of the Mini Light. This model has one large preheater 1.900L.

Application can be done on both sides with the newly developed transversal gun carrier, which is hydraulically movable from side to side. The gun carrier is operated from the truck cabin. The advantages of this solution are that only one extruder /set of spray guns are kept warm all the time besides the economy aspect to have only one extruder/set of spray guns to maintain.

We combine the full RME technology and safety issue in all aspects. The machine is still operated from inside the truck cabin.

Also, this model is equipped with the well known RME-pump, a hydraulically driven compressor, camera system for supervision, heat-oil system and glass bead system.

This model can be equipped with

- two alternative filling system, either with bigbags or with the pump-filling system when filling from separate boiler truck.
- Extruder 30-50 cm
- Spray guns 1-3 units
- Flexidot 20-45 cm.

TECHNICAL SPEC.

| Length: | ~7,0 m |
|--------------------------|-----------------------------|
| Wheel base chassie: | min 4,3 m |
| Width: | 2,55 m |
| Height: | 3,7-3,9 m |
| Weight, tara incl truck: | 12.500 kg |
| Weight, allowed: | 18.000 kg |
| Melting set: | 1x1.900L |
| Control Box: | RME |
| Extruder: | max 50cm |
| Spray block: | max 3pc |
| Flexidot: | max 45cm |
| Bead guns: | 2-3pc |
| Bead tank: | 415-470L |
| Production pump: | RME 120L/min |
| Compressor: | Hydraulic 5-7m ³ |
| Pointer: | Hydraulic/Pneumatic |
| Burners: | Riello 230V |
| Temp regulators: | CAN-BUS |