

PREHEATERS & MELTING SETS



GENERAL	TECHNICAL SPEC.	
All preheaters and melting sets are indirectly heated with an oil jacket. The heating is done by either oil or gas burner(s). An additional electrical heater can be added to maintain heat during non-working hours. All preheaters have thermostats for both oil and thermoplastic material. They are also fitted with a	Preheater sizes:	400L 500L 600L 800L 950L 1.050L 1.200L
protection against over-heating. The agitator could be designed for powder or block material and is always attached with double bearings on top making the bottom	Melting set sizes:	1.600L 1.900L 2x400L
sealed and leak free. The motion is done with hydraulic or electric motors. The mixing can be done with an automated program which alters directions and speed making the melting process more efficient. The material outlet has an oil jacket and could be handled by hand cleating program ties on		2x500L 2x600L 2x800L 2x950L 2x1.050L 2x1.200L 2x1.600L
be handled by hand, electrics, pneumatics or hydraulics. All melting sets can be equipped with a bigbagemptier for fast re-filling with powder material	Heating oil:	2x1.900L 2x1.900L Porta 30P
using a small crane. Filling systems with pumps are available with different capacities and always include a heat oil	Pump filling system:	50-200L/min

pump for heat circulation.

Fax. +46 40 315889