

MELTING SET PH400+SPP11d FRAME BUILT



Length:

TECHNICAL SPEC. GENERAL

Low-built melting set on frame for bitumenbased sealant, mastic asphalt and thermoplastic.

Ideally mounted on trailer 2.700-3.500 kg. The preheater is oil-jacketed and has a strong hydraulic agitator to handle hard blockmaterials or powder.

Large filling lid, low and ergonomically placed at the rear.

Heating with oil burner in the preheater's base. Out-let with manual valve.

Hydraulic hand controls for the preheater to control agitation direction and speed.

Integrated Silent Power Pack (SPP) on the same frame. The engine is silent with noiseproof capsule, which reduces the noise level substantially.

The SPP provides diesel to the burners, hydraulic power to the agitators and electrics for the thermostats etc

This equipment is CE-approved.

ca 1,30 m Width: Height.: ca 1,75 m Weight: 1.400 kg Preheater volume: 400L Heating: Riello oil burner 230V Indirect heated: Heating oil Temp regulators: For oil and material (2) Agitation engine: 630cc Outlet preheater: Manual valve Hatz 11hp diesel Engine: Silent capsule engine: Hatz original Start battery: Included Hydraulic pump: On engine Oil cooler: Included 230V-12V incl inverter Electrics: Hydraulic tank: 75L Diesel tank: 75L

ca 2,55 m

Road Marking/Maintenance Equipment of Sweden AB

www.rme.se Käglingev. 33 213 76 Malmö Sweden Tel 0046 40 315 880